



**IEEE Standard for
Information technology—
Telecommunications and information
exchange between systems—
Local and metropolitan area networks—
Specific requirements**

**Part 15.4: Wireless Medium Access Control
(MAC) and Physical Layer (PHY)
Specifications for Low-Rate Wireless
Personal Area Networks (WPANs)**

**Amendment 2: Alternative Physical Layer Extension
to support one or more of the Chinese 314–316 MHz,
430–434 MHz, and 779–787 MHz bands**

IEEE Computer Society

Sponsored by the
LAN/MAN Standards Committee

IEEE
3 Park Avenue
New York, NY 10016-5997, USA

17 April 2009

IEEE Std 802.15.4c™-2009
(Amendment to
IEEE Std 802.15.4™-2006)

802.15.4c™

IEEE Std 802.15.4c™-2009

(Amendment to
IEEE Std 802.15.4™-2006)

**IEEE Standard for
Information technology—
Telecommunications and information
exchange between systems—
Local and metropolitan area networks—
Specific requirements**

**Part 15.4: Wireless Medium Access Control (MAC)
and Physical Layer (PHY) Specifications for
Low-Rate Wireless Personal Area Networks
(WPANs)**

**Amendment 2: Alternative Physical Layer Extension
to support one or more of the Chinese 314–316 MHz,
430–434 MHz, and 779–787 MHz bands**

Sponsor

**LAN/MAN Standards Committee
of the
IEEE Computer Society**

Approved 19 March 2009

IEEE-SA Standards Board

Abstract: This amendment defines alternate PHY and modifications to the MAC needed to support the PHY that complies with the applicable Chinese regulations, Radio Management of P. R. of China doc. # 6326360786867187500 or current document, for one or more of the 314–316 MHz, 430–434 MHz, and 779–787 MHz frequency bands.

Keywords: ad hoc network, low data rate, low power, LR-WPAN, mobility, PAN, personal area network, radio frequency, RF, short range, wireless, wireless personal area network, WPAN

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2009 by the Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 17 April 2009. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

The *Bluetooth* word mark, figure mark, and combination mark are all trademarks that are owned by the Bluetooth SIG.

PDF: ISBN 978-0-7381-5913-3 STD95911
Print: ISBN 978-0-7381-5914-0 STDPD95911

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

Use of an IEEE Standard is wholly voluntary. The IEEE disclaims liability for any personal injury, property or other damage, of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, or reliance upon this, or any other IEEE Standard document.

The IEEE does not warrant or represent the accuracy or content of the material contained herein, and expressly disclaims any express or implied warranty, including any implied warranty of merchantability or fitness for a specific purpose, or that the use of the material contained herein is free from patent infringement. IEEE Standards documents are supplied **“AS IS.”**

The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE Standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard. Every IEEE Standard is subjected to review at least every five years for revision or reaffirmation. When a document is more than five years old and has not been reaffirmed, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE Standard.

In publishing and making this document available, the IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity. Nor is the IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing this, and any other IEEE Standards document, should rely upon his or her independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

Interpretations: Occasionally questions may arise regarding the meaning of portions of standards as they relate to specific applications. When the need for interpretations is brought to the attention of IEEE, the Institute will initiate action to prepare appropriate responses. Since IEEE Standards represent a consensus of concerned interests, it is important to ensure that any interpretation has also received the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to interpretation requests except in those cases where the matter has previously received formal consideration. A statement, written or oral, that is not processed in accordance with the IEEE-SA Standards Board Operations Manual shall not be considered the official position of IEEE or any of its committees and shall not be considered to be, nor be relied upon as, a formal interpretation of the IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position, explanation, or interpretation of the IEEE.

Comments for revision of IEEE Standards are welcome from any interested party, regardless of membership affiliation with IEEE. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Comments on standards and requests for interpretations should be submitted to the following address:

Secretary, IEEE-SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854
USA

Authorization to photocopy portions of any individual standard for internal or personal use is granted by The Institute of Electrical and Electronics Engineers, Inc., provided that the appropriate fee is paid to Copyright Clearance Center. To arrange for payment of licensing fee, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Introduction

This introduction is not part of IEEE Std 802.15.4c-2009, IEEE Standard for Information technology—Telecommunications and information exchange between systems—Local and metropolitan area networks—Specific requirements—Part 15.4: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications for Low-Rate Wireless Personal Area Networks (LR-WPANS)—Amendment 2: Alternative Physical Layer Extension to support one or more of the Chinese 314–316 MHz, 430–434 MHz, and 779–787 MHz bands.

This amendment specifies alternate PHYs in addition to those of the IEEE Std 802.15.4-2006 and IEEE Std 802.15.4a™-2007. These alternate PHYs are specified for the Chinese 780 MHz band.

Notice to users

Laws and regulations

Users of these documents should consult all applicable laws and regulations. Compliance with the provisions of this standard does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

This document is copyrighted by the IEEE. It is made available for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making this document available for use and adoption by public authorities and private users, the IEEE does not waive any rights in copyright to this document.

Updating of IEEE documents

Users of IEEE standards should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. An official IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect. In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE Standards Association website at <http://ieeexplore.ieee.org/xpl/standards.jsp>, or contact the IEEE at the address listed previously.

For more information about the IEEE Standards Association or the IEEE standards development process, visit the IEEE-SA website at <http://standards.ieee.org>.

Errata

Errata, if any, for this and all other standards can be accessed at the following URL: <http://standards.ieee.org/reading/ieee/updates/errata/index.html>. Users are encouraged to check this URL for errata periodically.

Interpretations

Current interpretations can be accessed at the following URL: <http://standards.ieee.org/reading/ieee/interp/index.html>.

Patents

Attention is called to the possibility that implementation of this amendment may require use of subject matter covered by patent rights. By publication of this amendment, no position is taken with respect to the existence or validity of any patent rights in connection therewith. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this amendment are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Participants

At the time this standard was sent to sponsor ballot, the IEEE P802.15™ Working Group had the following voting members:

Robert F. Heile, *Chair*
Rick Alfvén, *Vice Chair*
Patrick W. Kinney, *Vice-Chair, Secretary*
James P. K. Gilb, *Technical Editor*
John R. Barr, *Treasurer*

Reed Fisher, *Task Group 3c Chair*
Philip E. Beecher, *Task Group 4d Chair*
Patrick W. Kinney, *Task Group 4e Chair*
Myung Lee, *Task Group 5 Chair*
Arthur Astrin, *Task Group 6 Chair*

Clinton C Powell, *Task Group 4c Chair*
Kuor-Hsin Chang, *Task Group 4c Vice Chair, Secretary, Technical Editor*
Jay Bain, *Task Group 4c Editor-in-Chief*
Liang Li, *Chinese WPAN Liaison*

Taehan Bae
Gal Basson
Tuncer Baykas
Bruce Bosco
Andre Bourdoux
Pat Carson
Eduardo Casas
Philippe Chambelin
Chang-Soon Choi
Carlos Cordeiro
Alexey Davydov
Paul Dixon
Kai Dombrowski
John Dorsey
Bas Driesen
Amal Ekbal
Yossi Erlich
Robert Fanfelle
John Farserotu
Yoshitsugu Fujita
Ryuhei Funada
Uhland Goebel
Giriraj Goyal
Eckhard Grass
Mark Grodzinsky
Vivek Gupta
Robert Hall
Christopher J. Hansen
Shinsuke Hara
Hiroshi Harada
Seockdeock Hong
Tian-Wei Huang
Ichirou Ida
Hideto Ikeda
Tetsushi Ikegami
Akio Iso

Beomjin Jeon
Young-Ae Jeon
Seong-Soon Joo
Chol Su Kang
Tae-Gyu Kang
Yasunao Katayama
Shuzo Kato
Stuart J. Kerry
Jaehwa Kim
Jae-Hyon Kim
Jinkyong Kim
Kihong Kim
Kyeongpyo Kim
Seong Kim
Yongsun Kim
Ryota Kimura
Kursat Kimyacioglu
Ryuji Kohno
Fumihide Kojima
Edwin Kwon
Hyoungjin Kwon
Ismail Lakkis
John Lampe
Zhou Lan
Jae Lee
Jeong Lee
Seonghee Lee
Taehoon Lee
Wooyong Lee
Daniel Lewis
Huan-Bang Li
Sheung Li
Yong Liu
Alexander Maltsev
Abbie Mathew
Taisuke Matsumoto
Michael Mcinnis

Michael McLaughlin
Dino Miniutti
Rajendra Moorti
Jorge Myszne
Yukimasa Nagai
Ken Naganuma
Chiu Ngo
Paul Nikolich
Yoshinori Nishiguchi
Hiroyo Ogawa
Jisung Oh
Laurent Ouvry
Pascal Pagani
Tae Rim Park
Maulin Patel
Stephane Pinel
Stephen Pope
Chang Woo Pyo
Xiangping Qin
Ivan Reede
Richard Roberts
Ali Sadri
Katsuyoshi Sato
Hirokazu Sawada
Kamran Sayrafian
Jean Schwoerer
Huai-Rong Shao
Stephen Shellhammer
Shusaku Shimada
Yukihiro Shimakata
Chang Sub Shin
Michael Sim
Harkirat Singh
Carl Stevenson
Paul Strauch
Chin Sum
Kazuaki Takahashi

Kenichi Takizawa
Arnaud Tonnerre
Ichihiko Toyoda
Jason Trachewsky
Solomon Trainin
Alberto Valdes Garcia

Magnus Wiklund
Gerald Wineinger
Ludwig Winkel
Eun Tae Won
Jongeun Won
Pengfei Xia

Kamya Yazdandoost
James Yee
Kaoru Yokoo
Su Yong
Zhan Yu
Bin Zhen
Chunhui Zhu

Major contributions were received from the following individuals:

Hendricus De Ruijter
Kiyoshi Fukui
Shigeru Fukunaga

Paul Gorday
Yasutaka Kawamoto
Zhongding Lei
Klaus Meyer

Frank Poegel
Benjamin Rolfe
Michael Schmidt

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Richard Alfvin
Butch Anton
Danilo Antonelli
Jay Bain
Philip E. Beecher
Vern Brethour
William Byrd
Jing Cao
James Carlo
Juan Carreon
Kuor-Hsin Chang
Keith Chow
Charles Cook
Todor Cooklev
Thomas Dineen
Sourav Dutta
Paul Eastman
Avraham Freedman
Devon Gayle
Michael Geipel
Theodore Georgantas
James P. K. Gilb
Randall Groves
Jose A. Gutierrez
C. Guy
Rainer Hach

Robert F. Heile
Marco Hernandez
Karl Heubaum
Ian Hilliard
Tetsushi Ikegami
Atsushi Ito
Raj Jain
Bobby Jose
Shinkyō Kaku
Assaf Kasher
Kurt Kermes
Stuart J. Kerry
Eunkyung Kim
Yongbum Kim
Patrick W. Kinney
Myung Lee
Jan-Ray Liao
Arthur Light
Chiwoo Lim
Jeffery Masters
Michael Mcinnis
Hiroyuki Nakase
Charles Ngethe
John Notor
Satoshi Obara
Okundu Omeni

Satoshi Oyama
Eldad Perahia
James Petranovich
Subburajan Ponnuswamy
Robert Poor
Clinton C Powell
Jayaram Ramasastry
Robert Robinson
Benjamin Rolfe
Randall Safier
Osman Sakr
Shigenobu Sasaki
Bartien Sayogo
Shusaku Shimada
Kapil Sood
Amjad Soomro
Thomas Starai
Rene Struik
Walter Struppler
Mark Sturza
Dmitri Varsanofiev
Prabodh Varshney
Stanley Wang
Andreas Wolf
Wenhao Zhu

When the IEEE-SA Standards Board approved this standard on 19 March 2009, it had the following membership:

Robert M. Grow, *Chair*

Steve M. Mills, *Past Chair*

Judith Gorman, *Secretary*

John Barr
Karen Bartleson
Victor Berman
Ted Burse
Richard DeBlasio
Andy Drozd
Mark Epstein

Alexander Gelman
Jim Hughes
Rich Hulet
Young Kyun Kim
Joseph L. Koepfinger*
John Kulick
David Law
Ted Olsen

Glenn Parsons
Ron Petersen
Chuck Powers
Thomas Prevost
Narayanan Ramachandran
Jon Rosdahl
Sam Sciacca

*Member Emeritus

Also included are the following nonvoting IEEE-SA Standards Board liaisons:

Satish K. Aggarwal, *NRC Representative*
Michael Janezic, *NIST Representative*
Howard Wolfman, *TAB Representative*

Don Messina
IEEE Standards Program Manager, Document Development

Michael D. Kipness
IEEE Standards Program Manager, Technical Program Development

Contents

2.	Normative references	1
4.	Acronyms and abbreviations	2
5.	General description	2
5.1	Introduction.....	2
5.4	Architecture	2
5.4.1	Physical layer (PHY)	2
6.	PHY specification	3
6.1	General requirements and definitions	3
6.1.1	Operating frequency range.....	3
6.1.2	Channel assignments.....	3
6.1.3	Minimum LIFS and SIFS periods.....	4
6.3	PPDU format.....	5
6.3.1	Preamble field	5
6.3.2	SFD field.....	5
6.6	868/915 MHz band binary phase-shift keying (BPSK) PHY specifications	5
6.6a	780 MHz band (optional) O-QPSK PHY specifications	5
6.6a.1	780 MHz band data rates	5
6.6a.2	Modulation and spreading	5
6.6a.3	780 MHz band radio specification.....	8
6.9	General radio specifications.....	9
	Annex D (normative) Protocol implementation conformance statement (PICS) proforma	11
	Annex E (informative) Coexistence with other IEEE standards and proposed standards	13
	Annex F (informative) Regulatory requirements.....	15
	Annex J (informative) MPSK PHY requirements	17

**IEEE Standard for
Information technology—
Telecommunications and information
exchange between systems—
Local and metropolitan area networks—
Specific requirements**

**Part 15.4: Wireless Medium Access Control (MAC)
and Physical Layer (PHY) Specifications for
Low-Rate Wireless Personal Area Networks
(WPANs)**

**Amendment 2: Alternative Physical Layer Extension
to support one or more of the Chinese 314–316 MHz,
430–434 MHz, and 779–787 MHz bands**

IMPORTANT NOTICE: This standard is not intended to ensure safety, security, health, or environmental protection in all circumstances. Implementers of the standard are responsible for determining appropriate safety, security, environmental, and health practices or regulatory requirements.

This IEEE document is made available for use subject to important notices and legal disclaimers. These notices and disclaimers appear in all publications containing this document and may be found under the heading "Important Notice" or "Important Notices and Disclaimers Concerning IEEE Documents." They can also be obtained on request from IEEE or viewed at <http://standards.ieee.org/IPR/disclaimers.html>.

EDITORIAL NOTE—The editing instructions contained in this amendment define how to merge the material contained therein into the existing base standard and its amendments to form the comprehensive standard.

The editing instructions are shown in **bold italic**. Four editing instructions are used: change, delete, insert, and replace. **Change** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed by using ~~strike through~~ (to remove old material) and underscore (to add new material). **Delete** removes existing material. **Insert** adds new material without disturbing the existing material. Insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. **Replace** is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editorial notes will not be carried over into future editions because the changes will be incorporated into the base standard

2. Normative references

Insert the following new normative reference alphabetically into Clause 2:

NITS/CWPAN Part 15.4, Chinese standard for the Wireless Medium Access Control (MAC) and the Physical Layer (PHY) Specifications for Low-Rate Wireless Personal Area Networks (Task number: 20070007-T-469), version D2, Clause 6.5.2.

4. Acronyms and abbreviations

Insert the following abbreviations alphabetically into Clause 4:

CWPAN	Chinese Wireless Personal Area Network
MPSK	M-ary Phase Shift Keying

5. General description

5.1 Introduction

Change the following item in the dashed list of 5.1 as follows:

- 16 channels in the 2450 MHz band, 30 channels in the 915 MHz band, 3 channels in the 868 MHz band, 14 overlapping chirp spread spectrum (CSS) channels in the 2450 MHz band, ~~and~~ 16 channels in three UWB bands (500 MHz and 3.1 GHz to 10.6 GHz), and 8 channels in the 780 MHz band.

5.4 Architecture

5.4.1 Physical layer (PHY)

Insert a new dashed list item at the end of the third paragraph dashed list in 5.4.1 as follows:

- 779–787 MHz (People’s Republic of China)

6. PHY specification

6.1 General requirements and definitions

Insert the following paragraph at the end of 6.1:

In further additions to the rates supported in IEEE Std 802.15.4-2006 and IEEE Std 802.15.4a-2007, two additional PHYs have been added. They are MPSK and O-QPSK PHYs operating in the Chinese 780 MHz band. The MPSK PHY is defined by NITS/CWPAN Part 15.4, Chinese standard for the Wireless Medium Access Control (MAC) and the Physical Layer (PHY) Specifications for Low-Rate Wireless Personal Area Networks (Task number: 20070007-T-469), which is included as a normative reference in Clause 2. An informative translation of the MPSK PHY specification as it relates to this standard is included in Annex J.

6.1.1 Operating frequency range

Change Table 1 (the entire table is not shown) as indicated:

Table 1—Frequency bands and data rates

PHY (MHz)	Frequency band (MHz)	Spreading parameters		Data parameters		
		Chip rate (kchip/s)	Modulation	Bit rate (kb/s)	Symbol rate (ksymbol/s)	Symbols
<u>780</u>	<u>779–787</u>	<u>1000</u>	<u>O-QPSK</u>	<u>250</u>	<u>62.5</u>	<u>16-ary Orthogonal</u>
<u>780</u>	<u>779–787</u>	<u>1000</u>	<u>MPSK</u>	<u>250</u>	<u>62.5</u>	<u>16-ary Orthogonal</u>
868/915	868–868.6	300	BPSK	20	20	Binary
	902–928	600	BPSK	40	40	Binary

Change the third paragraph in 6.1.1 as shown:

This standard is intended to conform with established regulations in Europe, Japan, Canada, China, and the United States. The regulatory documents listed below are for information only and are subject to change and revisions at any time. ~~IEEE 802.15.4 and IEEE 802.15.4a~~ Devices conforming to this standard shall also comply with specific regional legislation. Additional regulatory information is provided in Annex F.

Insert the following new list at the end of the current lists in 6.1.1:

China:

- Approval standards: The Radio Management Bureau of the Chinese Information Department, China-Document: Doc. # 6326360786867187500

6.1.2 Channel assignments

Insert the following new subclause after 6.1.2.1b:

6.1.2.1c Channel numbering for 779–787 MHz band

For channel page 5, eight channels numbered 0 to 7 are available across 780 MHz band. The center frequency of these channels is defined as follows:

$$F_c = 780 + 2k \text{ in megahertz, for } k = 0, \dots, 3$$

$$F_c = 780 + 2(k - 4) \text{ in megahertz, for } k = 4, \dots, 7$$

where k is the channel number.

6.1.2.2 Channel pages

Change the first sentence of 6.1.2.2 as indicated:

A total of 32 channel pages are available with channel pages 3 to 31 being reserved for future use.

Change Table 2 (the entire table is not shown) as indicated:

Table 2—Channel page and channel number

Channel page (decimal)	Channel page (binary) (b31,b30,b29,b28,b27)	Channel number(s) (decimal)	Channel number description
<u>5</u>	<u>00101</u>	<u>0–3</u>	<u>Channels 0 to 3 are in 780 MHz band using O-QPSK</u>
		<u>4–7</u>	<u>Channels 4 to 7 are in the 780 MHz band using MPSK</u>
36 –31	00110–11111	Reserved	Reserved

6.1.3 Minimum LIFS and SIFS periods

Change Table 3 (the entire table is not shown) as indicated:

Table 3—Minimum LIFS and SIFS period

PHY	<i>macMinLIFSPeriod</i>	<i>macMinSIFSPeriod</i>	Units
<u>779–787 MHz O-QPSK</u>	<u>40</u>	<u>12</u>	<u>Symbols</u>
<u>779–787 MHz MPSK</u>	<u>40</u>	<u>12</u>	<u>Symbols</u>
868–868.6 MHz BPSK	40	12	Symbols

6.3 PPDU format

6.3.1 Preamble field

Change Table 19 (the entire table is not shown) as indicated:

Table 19—Preamble field length

PHY	Length		Duration (uS)
<u>779–787 MHz O-QPSK</u>	<u>4 octets</u>	<u>8 symbols</u>	<u>128</u>
<u>779–787 MHz MPSK</u>	<u>4 octets</u>	<u>8 symbols</u>	<u>128</u>
868–868.6 MHz BPSK	4 octets	32 symbols	1600

6.3.2 SFD field

Change Table 20 (the entire table is not shown) as indicated:

Table 20—SFD field length (except for ASK, CSS, and UWB PHYs)

PHY	Length	
<u>779–787 MHz O-QPSK</u>	<u>1 octet</u>	<u>2 symbols</u>
<u>779–787 MHz MPSK</u>	<u>1 octet</u>	<u>2 symbols</u>
868–868.6 MHz BPSK	1 octet	8 symbols

6.6 868/915 MHz band binary phase-shift keying (BPSK) PHY specifications

Insert after 6.6.3.5 the following new subclauses (6.6a through 6.6a.3.5):

6.6a 780 MHz band (optional) O-QPSK PHY specifications

6.6a.1 780 MHz band data rates

The data rate of the O-QPSK PHY shall be 250 kb/s when operating in the 780 MHz band.

6.6a.2 Modulation and spreading

The O-QPSK PHY employs a 16-ary quasi-orthogonal modulation technique. During each data symbol period, four information bits are used to select one of 16 nearly orthogonal PN sequences to be transmitted. The PN sequences for successive data symbols are concatenated, and the aggregate chip sequence is modulated onto the carrier using O-QPSK.

6.6a.2.1 Reference modulator diagram

The functional block diagram in Figure 21a is provided as a reference for specifying the 780 MHz band PHY modulation and spreading functions. The number in each block refers to the subclause that describes

that function. Each bit in the PPDU shall be processed through the bit-to-symbol mapping, symbol-to-chip mapping, and modulation functions in octet-wise order, beginning with the Preamble field and ending with the last octet of the PSDU. Within each octet, the LSB, b_0 , is processed first and the MSB, b_7 , is processed last.




Figure 21a—Modulation and spreading functions

6.6a.2.2 Bit-to-symbol mapping

All binary data contained in the PPDU shall be encoded using the modulation and spreading functions shown in Figure 21a. This subclause describes how binary information is mapped into data symbols.

The 4 LSBs (b_0, b_1, b_2, b_3) of each octet shall map into one data symbol, and the 4 MSBs (b_4, b_5, b_6, b_7) of each octet shall map into the next data symbol. Each octet of the PPDU is processed through the modulation and spreading functions (see Figure 21a) sequentially, beginning with the Preamble field and ending with the last octet of the PSDU. Within each octet, the least significant symbol (b_0, b_1, b_2, b_3) is processed first, and the most significant symbol (b_4, b_5, b_6, b_7) is processed second.

6.6a.2.3 Symbol-to-chip mapping

Each data symbol shall be mapped into a 16-chip PN sequence as specified in Table 29a.

Table 29a—Symbol-to-chip mapping for O-QPSK

Data symbol (decimal)	Data symbol (binary) ($b_0 b_1 b_2 b_3$)	Chip values ($c_0 c_1 \dots c_{14} c_{15}$)
0	0 0 0 0	0 0 1 1 1 1 1 0 0 0 1 0 0 1 0 1
1	1 0 0 0	0 1 0 0 1 1 1 1 1 0 0 0 1 0 0 1
2	0 1 0 0	0 1 0 1 0 0 1 1 1 1 1 0 0 0 1 0
3	1 1 0 0	1 0 0 1 0 1 0 0 1 1 1 1 1 0 0 0
4	0 0 1 0	0 0 1 0 0 1 0 1 0 0 1 1 1 1 1 0
5	1 0 1 0	1 0 0 0 1 0 0 1 0 1 0 0 1 1 1 1
6	0 1 1 0	1 1 1 0 0 0 1 0 0 1 0 1 0 0 1 1
7	1 1 1 0	1 1 1 1 1 0 0 0 1 0 0 1 0 1 0 0
8	0 0 0 1	0 1 1 0 1 0 1 1 0 1 1 1 0 0 0 0
9	1 0 0 1	0 0 0 1 1 0 1 0 1 1 0 1 1 1 0 0
10	0 1 0 1	0 0 0 0 0 1 1 0 1 0 1 0 1 1 0 1 1 1

Table 29a—Symbol-to-chip mapping for O-QPSK (continued)

Data symbol (decimal)	Data symbol (binary) (b ₀ b ₁ b ₂ b ₃)	Chip values (c ₀ c ₁ ... c ₁₄ c ₁₅)
11	1 1 0 1	1 1 0 0 0 0 0 1 1 0 1 0 1 1 0 1
12	0 0 1 1	0 1 1 1 0 0 0 0 0 1 1 0 1 0 1 1
13	1 0 1 1	1 1 0 1 1 1 0 0 0 0 0 1 1 0 1 0
14	0 1 1 1	1 0 1 1 0 1 1 1 0 0 0 0 0 1 1 0
15	1 1 1 1	1 0 1 0 1 1 0 1 1 1 0 0 0 0 0 1

6.6a.2.4 O-QPSK modulation

The chip sequences representing each data symbol are modulated onto the carrier using O-QPSK with raised cosine pulse shaping. Even-indexed chips are modulated onto the in-phase (I) carrier and odd-indexed chips are modulated onto the quadrature-phase (Q) carrier. Because each data symbol is represented by a 16-chip sequence, the chip rate is 16 times the symbol rate. To form the offset between I-phase and Q-phase chip modulation, the Q-phase chips shall be delayed by T_c with respect to the I-phase chips (see Figure 21b), where T_c is the inverse of the chip rate.




Figure 21b—O-QPSK chip offsets

6.6a.2.5 Pulse shape

The raised cosine pulse shape with roll-off factor of $r = 0.8$ is used to represent each baseband chip and is described by Equation (4a).

$$p(t) = \begin{cases} \frac{\sin(\pi t/T_c)}{\pi t/T_c} \times \frac{\cos(r\pi t/T_c)}{1 - 4r^2 t^2/T_c^2}, & t \neq 0 \\ 1, & t = 0 \end{cases} \tag{4a}$$

Given the discrete-time sequence $\{c_k\}_{k=-\infty}^{\infty}$ of consecutive real-valued chip samples, the continuous-time pulse shaped complex baseband signal is given by Equation (4b).

$$y(t) = \sum_{k=-\infty}^{\infty} c_{2k} p(t - 2kT_c) + j c_{2k+1} p(t - 2kT_c - T_c) \tag{4b}$$

6.6a.2.6 Chip transmission order

During each symbol period, the least significant chip, c_0 , is transmitted first, and the most significant chip, c_{15} , is transmitted last.

6.6a.3 780 MHz band radio specification

6.6a.3.1 Operating frequency range

The 780 MHz O-QPSK PHY operates in the 779–787 MHz frequency band.

6.6a.3.2 Transmit PSD mask

When operating in the 780 MHz band, the transmitted spectral products shall be less than the limits specified in Table 29b. For both relative and absolute limits, average spectral power shall be measured using a 100 kHz resolution bandwidth. For the relative limit, the reference level shall be the highest average spectral power measured within ± 600 kHz of the carrier frequency f_c .

Table 29b—780 MHz band O-QPSK PHY transmit PSD limits

Frequency	Relative limit	Absolute limit
$ f - f_c > 1.2$ MHz	–20 dB	–20 dBm

6.6a.3.3 Symbol rate

The O-QPSK PHY symbol rate shall be 62.5 ksymbol/s when operating in the 780 MHz band with an accuracy of ± 40 ppm.

6.6a.3.4 Receiver sensitivity

Under the conditions specified in 6.1.7, a compliant device shall be capable of achieving a sensitivity of –85 dBm or better.

6.6a.3.5 Receiver jamming resistance

The minimum jamming resistance levels are given in Table 29c. The adjacent channel is one on either side of the desired channel that is closest in frequency to the desired channel, and the alternate channel is one more removed from the adjacent channel. For example, when channel 2 is the desired channel, channel 1 and channel 3 are the adjacent channels, and channel 0 is the alternate channel.

Table 29c—Minimum receiver jamming resistance requirements for 780 MHz O-QPSK PHY

Adjacent channel rejection	Alternate channel rejection
0 dB	30 dB

The adjacent channel rejection shall be measured as follows: the desired signal shall be a compliant 780 MHz IEEE 802.15.4 O-QPSK PHY signal, as defined by 6.6a.2, of pseudo-random data. The desired signal is input to the receiver at a level 3 dB above the maximum allowed receiver sensitivity given in 6.6a.3.4.

In either the adjacent or the alternate channel, a compliant signal, as defined by 6.6a.2, is input at the relative level specified in Table 29c. The test shall be performed for only one interfering signal at a time. The receiver shall meet the error rate criteria defined in 6.1.7 under these conditions.

Change the text in 6.9 as shown (based on IEEE Std 802.15.4a text):

6.9 General radio specifications

The specifications in 6.9.1 through 6.9.9 apply to the 2450 MHz DS PHY described in 6.5.1 through 6.5.3, the CSS PHY described in 6.5a, the UWB PHY described in 6.8a, ~~and~~ the 868/915 MHz PHYs described in 6.6 through 6.8, and the 780 MHz PHYs described in 6.6a and Clause 2 and, with the exception of 6.9.3 and 6.9.5, apply to all PHY implementations including the alternate PHYs. The specification of 6.9.3 does not apply to the CSS PHY nor the UWB PHY. The specification of 6.9.5 does not apply to the UWB PHY.

Annex D

(normative)

Protocol implementation conformance statement (PICS) proforma¹

D.1 Introduction

D.1.2 Scope

Change the text of D.1.1 as shown:

This annex provides the PICS proforma for IEEE Std 802.15.4-2006 and IEEE Std 802.15.4a amendment in compliance with the relevant requirements, and in accordance with the relevant guidance, given in ISO/IEC 9646-7:1995.

D.1.2 Purpose

Change the first paragraph of D.1.2 as shown:

The supplier of a protocol implementation claiming to conform to IEEE Std 802.15.4-2006 and IEEE Std 802.15.4a amendment shall complete the following PICS proforma and accompany it with the information necessary to identify fully both the supplier and the implementation.

D.5 Identification of the protocol

Change the text of D.5 as shown:

This PICS proforma applies to IEEE Std 802.15.4-2006 and IEEE Std 802.15.4a amendment.

D.7 PICS proforma tables

Change the third sentence in D.7 as shown:

The first subclause contains the major roles for a device compliant with IEEE 802.15.4-2006 and IEEE 802.15.4a amendment.

¹*Copyright release for PICS proformas:* Users of this standard may freely reproduce the PICS proforma in this annex so that it can be used for its intended purpose and may further publish the completed PICS.

D.7.2 Major capabilities for the PHY

D.7.2.3 Radio frequency (RF)

Insert after the RF4.3 row the following new rows in Table D.4 and add a new note entry to the final row (the entire table is not shown):

Table D.4—Radio frequency (RF)

Item number	Item description	Reference	Status	Support		
				N/A	Yes	No
<u>RF5</u>	<u>780 MHz band PHYs</u>	<u>5.4.1, Clause 6, Table 1</u>	<u>O.3</u>			
<u>RF5.1</u>	<u>Offset quadrature phase-shift keying (O-QPSK) PHY</u>	<u>6.6a</u>	<u>O.6</u>			
<u>RF5.2</u>	<u>M-ary phase-shift keying (MPSK) PHY</u>	<u>Clause 2</u>	<u>O.6</u>			
<u>O.3 At least one of these features shall be supported.</u> <u>O.5 At least one of these features shall be supported.</u> <u>O.6 At least one of these features shall be supported.</u>						

Annex E

(informative)

Coexistence with other IEEE standards and proposed standards

E.1 Introduction

Insert the following new paragraph at the end of E.1:

This is the first IEEE 802[®] standard defining use of the 780 MHz band (779 MHz to 787 MHz) in China and as such coexistence is not a practical issue at this time. However, the two PHYs specified for use in the 780 MHz band use the exact same channel plan; hence they can potentially cause interference to each other. Due to the short duration (burst nature) of IEEE 802.15.4 packets and use of CSMA-CA, coexistence is not considered to be a problem for the two PHYs when they share a common channel. Similar examples of this are shown in E.5.

Annex F

(informative)

Regulatory requirements

F.2 IEEE 802.15.4a UWB

F.2.4.3 Technical requirements on radio equipment

Insert the following new subclause after F.2.4.3:

F.3 Applicable Chinese rules

Operation in the 779–787 MHz band in China is defined by the Radio Management of P. R. of China in the Technical Requirements for Micropower (Short Distance) Radio Equipment (Doc. # 6326360786867187500). The original document and any version superseding it should be used for a final disposition on the rules. An English translation of the applicable sections are covered in this clause in order to give the reader a familiarity with the regulations governing the use of the 779–787 MHz band in China.

F.3.1 Category F equipment

Category F equipment refers to other short distance radio equipment rather than digital cordless telephone, Bluetooth^{®2} equipment and wireless LAN equipment, working at the range of 2400–2483.5 MHz.

- a) Working frequency: 2400–2483.50 MHz
- b) Transmitting power limit: 10 mW (EIRP)
- c) Frequency tolerance: 75 kHz

F.3.2 Radio control devices for all kinds of civil equipment

Radio controlled devices are prohibited for use for toys and models, but can be used for civilian equipment for the following working frequencies:

- a) Working frequency: 314–316 MHz, 430–432 MHz, and 433.00–434.79 MHz
Transmitting power limit: 10 mW (EIRP)
Occupied bandwidth: no greater than 400 kHz
- b) Working frequency: 779–787 MHz
Transmitting power limit: 10 mW (EIRP)
No occupied bandwidth requirement

²The *Bluetooth* word mark, figure mark, and combination mark are all trademarks that are owned by the Bluetooth SIG.

F.3.3 General requirements

This subclause outlines spurious radiation emission limits (the demarcation between spurious radiation and out of band radiation is the carrier frequency ± 2.5 multiples of carrier frequency). (See Table F.17.)

Table F.17—Spurious radiation emission measurement frequency range

Working frequency range	Spurious radiation emission measurement frequency range:	
	Lower limit	Upper limit
600 MHz–2.5 GHz	30 MHz	12.75 GHz

Table F.18—Transmitter in transmission state at the maximum power

Frequency range	Test bandwidth	Limit	Detection method
30 MHz–1 GHz	100 kHz (3 dB)	–36 dBm	Effective value
1 GHz–40 GHz	1 MHz (3 dB)	–30 dBm	Effective value

Table F.19—Transmitter in standby or idle state

Frequency range	Test bandwidth	Limit	Detection method
30 MHz–1 GHz	100 kHz (3 dB)	–47 dBm	Effective value
>1 GHz	1 MHz (3 dB)		

NOTE—Magnetic field test is performed at open area and radiation power test is performed at full anechoic chamber. For the equipment the working frequency of which is below 30 MHz, the emission state can be set to single frequency (SF) emission.³

For the frequency bands above 30 MHz, the radiation power at the upper/lower limits of the specified working frequency is no more than –80 dBm/Hz (EIRP).

³Notes in text, tables, and figures are given for information only and do not contain requirements needed to implement the standard.

Annex J

(informative)

MPSK PHY requirements

The following is an informative translation of the MPSK PHY, which is one of the co-alternative PHYs in the CWPAN specification. Another co-alternative PHY in the CWPAN specification is the O-QPSK PHY specified in 6.6a. The CWPAN specification is NITS/CWPAN Part 15.4, Chinese standard for the Wireless Medium Access Control (MAC) and the Physical Layer (PHY) Specifications for Low-Rate Wireless Personal Area Networks (Task number: 20070007-T-469).

J.1 780 MHz band data rates

The data rate of the MPSK PHY is 250 kb/s when operating in the 780 MHz band.

J.2 Modulation and spreading

The MPSK PHY employs a 16-ary orthogonal modulation technique. During each data symbol period, four information bits are used to select one of 16 orthogonal PN sequences to be transmitted. The PN sequences for successive data symbols are concatenated, and the aggregate chip phase is modulated onto the carrier using PSK.

J.2.1 Reference modulator diagram

The functional block diagram in Figure J.1 is provided as a reference for specifying the 780 MHz band MPSK PHY modulation and spreading functions. The number in each block refers to the subclause that describes that function. Each bit in the PPDU is processed through the bit-to-symbol mapping, symbol-to-chip mapping, pre-processing, and modulation functions in octet-wise order, beginning with the Preamble field and ending with the last octet of the PSDU. Within each octet, the LSB, b_0 , is processed first and the MSB, b_7 , is processed last.




Figure J.1—Modulation and spreading functions

J.2.2 Bit-to-symbol mapping

All binary data contained in the PPDU is encoded using the modulation and spreading functions shown in Figure J.1. This subclause describes how binary information is mapped into data symbols.

The 4 LSBs (b_0, b_1, b_2, b_3) of each octet is mapped into one data symbol, and the 4 MSBs (b_4, b_5, b_6, b_7) of each octet is mapped into the next data symbol. Each octet of the PPDU is processed through the modulation and spreading functions (see Figure J.1) sequentially, beginning with the Preamble field and ending with the last octet of the PSDU. Within each octet, the least significant symbol (b_0, b_1, b_2, b_3) is processed first, and the most significant symbol (b_4, b_5, b_6, b_7) is processed second.

J.2.3 Symbol-to-chip mapping

Each data symbol is mapped into a 16-chip PN sequence as specified in Table J.1.

Table J.1—Symbol-to-chip mapping for MPSK

Data symbol (decimal)	Data symbol (binary) ($b_0 b_1 b_2 b_3$)	Chip phases ($c_0 c_1 \dots c_{14} c_{15}$)
0	0 0 0 0	$0 \frac{\pi}{4} \frac{\pi}{16} \frac{9\pi}{16} \pi \frac{7\pi}{16} \frac{\pi}{4} \frac{15\pi}{16} 0 \frac{15\pi}{16} \frac{\pi}{4} \frac{7\pi}{16} \pi \frac{9\pi}{16} \frac{\pi}{4} \frac{\pi}{16}$
1	1 0 0 0	$\frac{\pi}{16} 0 \frac{\pi}{4} \frac{\pi}{16} \frac{9\pi}{16} \pi \frac{7\pi}{16} \frac{\pi}{4} \frac{15\pi}{16} 0 \frac{15\pi}{16} \frac{\pi}{4} \frac{7\pi}{16} \pi \frac{9\pi}{16} \frac{\pi}{4}$
2	0 1 0 0	$\frac{\pi}{4} \frac{\pi}{16} 0 \frac{\pi}{4} \frac{\pi}{16} \frac{9\pi}{16} \pi \frac{7\pi}{16} \frac{\pi}{4} \frac{15\pi}{16} 0 \frac{15\pi}{16} \frac{\pi}{4} \frac{7\pi}{16} \pi \frac{9\pi}{16}$
3	1 1 0 0	$\frac{9\pi}{16} \frac{\pi}{4} \frac{\pi}{16} 0 \frac{\pi}{4} \frac{\pi}{16} \frac{9\pi}{16} \pi \frac{7\pi}{16} \frac{\pi}{4} \frac{15\pi}{16} 0 \frac{15\pi}{16} \frac{\pi}{4} \frac{7\pi}{16} \pi$
4	0 0 1 0	$\pi \frac{9\pi}{16} \frac{\pi}{4} \frac{\pi}{16} 0 \frac{\pi}{4} \frac{\pi}{16} \frac{9\pi}{16} \pi \frac{7\pi}{16} \frac{\pi}{4} \frac{15\pi}{16} 0 \frac{15\pi}{16} \frac{\pi}{4} \frac{7\pi}{16}$
5	1 0 1 0	$\frac{7\pi}{16} \pi \frac{9\pi}{16} \frac{\pi}{4} \frac{\pi}{16} 0 \frac{\pi}{4} \frac{\pi}{16} \frac{9\pi}{16} \pi \frac{7\pi}{16} \frac{\pi}{4} \frac{15\pi}{16} 0 \frac{15\pi}{16} \frac{\pi}{4}$
6	0 1 1 0	$\frac{\pi}{4} \frac{7\pi}{16} \pi \frac{9\pi}{16} \frac{\pi}{4} \frac{\pi}{16} 0 \frac{\pi}{4} \frac{\pi}{16} \frac{9\pi}{16} \pi \frac{7\pi}{16} \frac{\pi}{4} \frac{15\pi}{16} 0 \frac{15\pi}{16}$
7	1 1 1 0	$\frac{15\pi}{16} \frac{\pi}{4} \frac{7\pi}{16} \pi \frac{9\pi}{16} \frac{\pi}{4} \frac{\pi}{16} 0 \frac{\pi}{4} \frac{\pi}{16} \frac{9\pi}{16} \pi \frac{7\pi}{16} \frac{\pi}{4} \frac{15\pi}{16} 0$
8	0 0 0 1	$0 \frac{15\pi}{16} \frac{\pi}{4} \frac{7\pi}{16} \pi \frac{9\pi}{16} \frac{\pi}{4} \frac{\pi}{16} 0 \frac{\pi}{4} \frac{\pi}{16} \frac{9\pi}{16} \pi \frac{7\pi}{16} \frac{\pi}{4} \frac{15\pi}{16}$
9	1 0 0 1	$\frac{15\pi}{16} 0 \frac{15\pi}{16} \frac{\pi}{4} \frac{7\pi}{16} \pi \frac{9\pi}{16} \frac{\pi}{4} \frac{\pi}{16} 0 \frac{\pi}{4} \frac{\pi}{16} \frac{9\pi}{16} \pi \frac{7\pi}{16} \frac{\pi}{4}$
10	0 1 0 1	$\frac{\pi}{4} \frac{15\pi}{16} 0 \frac{15\pi}{16} \frac{\pi}{4} \frac{7\pi}{16} \pi \frac{9\pi}{16} \frac{\pi}{4} \frac{\pi}{16} 0 \frac{\pi}{4} \frac{\pi}{16} \frac{9\pi}{16} \pi \frac{7\pi}{16}$
11	1 1 0 1	$\frac{7\pi}{16} \frac{\pi}{4} \frac{15\pi}{16} 0 \frac{15\pi}{16} \frac{\pi}{4} \frac{7\pi}{16} \pi \frac{9\pi}{16} \frac{\pi}{4} \frac{\pi}{16} 0 \frac{\pi}{4} \frac{\pi}{16} \frac{9\pi}{16} \pi$
12	0 0 1 1	$\pi \frac{7\pi}{16} \frac{\pi}{4} \frac{15\pi}{16} 0 \frac{15\pi}{16} \frac{\pi}{4} \frac{7\pi}{16} \pi \frac{9\pi}{16} \frac{\pi}{4} \frac{\pi}{16} 0 \frac{\pi}{4} \frac{\pi}{16} \frac{9\pi}{16}$
13	1 0 1 1	$\frac{9\pi}{16} \pi \frac{7\pi}{16} \frac{\pi}{4} \frac{15\pi}{16} 0 \frac{15\pi}{16} \frac{\pi}{4} \frac{7\pi}{16} \pi \frac{9\pi}{16} \frac{\pi}{4} \frac{\pi}{16} 0 \frac{\pi}{4} \frac{\pi}{16}$

Table J.1—Symbol-to-chip mapping for MPSK (continued)

Data symbol (decimal)	Data symbol (binary) (b ₀ b ₁ b ₂ b ₃)	Chip phases (c ₀ c ₁ ... c ₁₄ c ₁₅)
14	0 1 1 1	$\frac{\pi}{16}$ $\frac{9\pi}{16}$ π $-\frac{7\pi}{16}$ $\frac{\pi}{4}$ $-\frac{15\pi}{16}$ 0 $-\frac{15\pi}{16}$ $\frac{\pi}{4}$ $-\frac{7\pi}{16}$ π $\frac{9\pi}{16}$ $\frac{\pi}{4}$ $\frac{\pi}{16}$ 0 $\frac{\pi}{4}$
15	1 1 1 1	$\frac{\pi}{4}$ $\frac{\pi}{16}$ $\frac{9\pi}{16}$ π $-\frac{7\pi}{16}$ $\frac{\pi}{4}$ $-\frac{15\pi}{16}$ 0 $-\frac{15\pi}{16}$ $\frac{\pi}{4}$ $-\frac{7\pi}{16}$ π $\frac{9\pi}{16}$ $\frac{\pi}{4}$ $\frac{\pi}{16}$ 0

J.2.4 Pre-processing

The chip sequence that the chip phase is mapped to consists of some DC value. To mitigate the DC effect, this pre-processing block subtracts each chip by the following value in Equation (J.1).

$$A_{DC} = \left(\frac{1}{4}\right) \exp\left(j\frac{\pi}{4}\right) \quad (J.1)$$

J.2.5 PSK modulation

The chip phases representing each data symbol are modulated onto the carrier using PSK with raised cosine pulse shaping. Because each data symbol is represented by a 16-chip sequence, the chip rate is 16 times the symbol rate.

J.2.6 Pulse shape

The raised cosine pulse shape with roll-off factor of $r = 0.5$ is used to represent each baseband chip and is described by Equation (J.2).

$$p(t) = \begin{cases} \frac{\sin(\pi t/T_c)}{\pi t/T_c} \times \frac{\cos(r\pi t/T_c)}{1 - 4r^2 t^2/T_c^2}, & t \neq 0 \\ 1, & t = 0 \end{cases} \quad (J.2)$$

Given the discrete-time sequence $\{\exp(jc_k)\}_{k=-\infty}^{\infty}$ of consecutive complex-valued chip samples, the continuous-time pulse shaped complex baseband signal is given by Equation (J.3).

$$y(t) = \sum_{k=-\infty}^{\infty} \exp(jc_k) p(t - kT_c) \quad (J.3)$$

where T_c is the inverse of the chip rate.

J.2.7 Chip transmission order

During each symbol period, the least significant chip phase, c_0 , is transmitted first, and the most significant chip phase, c_{15} , is transmitted last.

J.3 780 MHz band radio specification

The transmit power (EIRP) is limited to 10 mW.

J.3.1 Operating frequency range

The 780 MHz MPSK PHY operates in the 779–787 MHz frequency band.

J.3.2 Transmit PSD mask

When operating in the 780 MHz band, the transmitted spectral products are less than the limits specified in Table J.2. For both relative and absolute limits, average spectral power is measured using a 100 kHz resolution bandwidth. For the relative limit, the reference level is the highest average spectral power measured within ± 600 kHz of the carrier frequency f_c .

Table J.2—780 MHz band MPSK PHY transmit PSD limits

Frequency	Relative limit	Absolute limit
$ f - f_c > 1.2$ MHz	–20 dB	–20 dBm

J.3.3 Symbol rate

The MPSK PHY symbol rate is 62.5 ksymbol/s when operating in the 780 MHz band with an accuracy of ± 40 ppm.

J.3.4 Receiver sensitivity

A compliant device is capable of achieving a sensitivity of –85 dBm or better for the definitions in Table J.3.

Table J.3—Receiver sensitivity definitions

Term	Definition of term	Conditions
Packet error rate (PER)	Average fraction of transmitted packets that are not correctly received.	– Average measured over random PSDU data.
Receiver sensitivity	Threshold input signal power that yields a specified PER.	– PSDU length = 20 octets. – PER < 1%. – Power measured at antenna terminals. – Interference not present.

J.3.5 Receiver jamming resistance

The minimum jamming resistance levels are given in Table J.4. The adjacent channel is one on either side of the desired channel that is closest in frequency to the desired channel, and the alternate channel is one more removed from the adjacent channel. For example, when channel 2 is the desired channel, channel 1 and channel 3 are the adjacent channels, and channel 0 is the alternate channels.

Table J.4—Minimum receiver jamming resistance requirements for 780 MHz MPSK PHY

Adjacent channel rejection	Alternate channel rejection
0 dB	30 dB

The adjacent channel rejection is measured as follows: the desired signal is a compliant 780 MHz IEEE 802.15.4 MPSK PHY signal, as defined by J.2, of pseudo-random data. The desired signal is input to the receiver at a level 3 dB above the maximum allowed receiver sensitivity given in J.3.4.

In either the adjacent or the alternate channel, a compliant signal, as defined by J.2, is input at the relative level specified in Table J.4. The test is performed for only one interfering signal at a time. The receiver will meet the error rate criteria defined in J.3.4 under these conditions.